

LUKA 8

LUKA8 is made from aluminium and has a stainless steel trim. LUKA8 uplights are designed for outdoor architectural lighting applications.

LUKA8 is designed with an array of LED chips and uses a clear tempered glass. The body is coated with twin layers of coating for enhanced corrosion resistance.

The fixture is available in various colour temperatures and beam angles. The product is offered in single colour and RGB with built-in driver.

DMX addressed during manufacture.



Colours Available

Cool White - 5000K			
Neutral White - 4000K			
Warm White - 2700K, 3000K			
Single Colours			
● Red	● Green	● Blue	● Amber
● ● ● RGB			

Optics Available

10°, 25°, 40°, 60°

Technical Specification		
Number of LEDs	9	12
System Power Consumption	20W	26W
LED Power Consumption	17W	22W
Input Voltage	220V 50/60Hz	
Luminaire Luminous Flux @4000K CRI80	1400lm	1800lm
Adjustability	Fixed	
Housing	Aluminium	
Trim	Stainless Steel	
Diffuser	Clear Tempered Glass	
Static Load	2000kg	
Driver	Integral	
Weight	4.5kg	
IP Rating	IP67	
Lamp Life L70	50,000 hours	
Operating Ambient Temp.	-20°C to +50°C	



Product Code

TRY - LUKA8 - 20W - 27K - 10 - IP67
 26W 30K 25
 40K 40
 50K 60
 RED
 BLU
 GRN
 AMB
 RGB

Product Code Example:

TRY-LUKA8-26W-30K-25-IP67

As part of our continuous product development we reserve the right to amend these specifications without prior notice.

Tryka L.E.D. Ltd., Unit 3 Station Works, Station Road, Shepreth, Nr. Royston, Herts, U.K SG8 6PZ. Tel: +44 (0) 1763 260666 www.tryka.com